# PROGRAMMABLE ROOM THERMOSTAT

# ambiente<sup>®</sup>

## more than underfloor

### **PRODUCT OVERVIEW**

The Ambiente Programmable Room Thermostat is our most popular model for the control of individual heating zones. The ability to set up the heating system to the most efficient pattern, as well as geared to the users lifestyle, as made this a popular choice for homeowners.

This model has 7-day programming function, with 4 time periods per day, pre-set by the user to meet their requirements. Other features include Holiday mode, lock function, frost mode.

The thermostat is available as 230v (PRT/E) and 12v (PRT/NE), working with UH2/UH3 or UH1 wiring centres respectively. This model is unique to Ambiente for the following reasons:

### **External temperature sensors:**

The Ambiente programmable thermostat can be used with remote air sensors, remote floor sensors, or both together - this meets the need where the air sensor is used to monitor the room temperature, and the floor sensor is used to limit the overall floor temperature in order to protect sensitive floor coverings.

Can be used for both wet and electric UFH: As this model can switch 16A, it is suitable for the control of both electric and hydronic/wet' UFH.

# Wed Com TEMP C C C

### Wiring

Our programmable thermostat requires 3 cores + earth of either mains/12v wiring.

### **Dimensions**

 $Height = 98mm \mid Width = 85mm \mid depth = 13mm$ 

Model Type	230v	230v		12v Network			
	PRT-E	PRT	PRT-E	DT-N	PRT-N	PRT-EN	
Temperature Range	05-35°C	05-35°C 05-95°F					
5/2 Day Programming	Yes	Yes	Yes	No	Yes	Yes	
7 Day Programming	Yes	Yes	Yes	No	Yes	Yes	
No. of Heating Levels	4	4	4	1	4	4	
Optimum Start	Yes	Yes	Yes	No	Yes	Yes	
Holiday Function	Yes	Yes	Yes	No	Yes	Yes	
Keylock	Yes	Yes	Yes	Yes	Yes	Yes	
Temperature Hold	Yes	Yes	Yes	No	Yes	No	
Temperature Override	Yes	Yes	Yes	Yes	Yes	Yes	
Temp Override Limit	Yes	Yes	Yes	Yes	Yes	Yes	
Frost Protection	Yes	Yes	Yes	Yes	Yes	Yes	
Networking Facility	No	No	No	Yes	Yes	Yes	
C/F Option	Yes	Yes	Yes	Yes	Yes	Yes	
Remote Air Sensor Connection	Yes	No	Yes	No	No	Yes	
Built In Air Sensor	Yes	Yes	Yes	Yes	Yes	Yes	
Floor Sensing Mode	Yes	No	Yes	No	No	Yes	
Floor Sensor Included	No	No	No	No	No	Yes	
Max Current	16A	3A	16A	3A	3A	3A	
Accuracy	+/-1C	+/-1C	+/-1C	+/-1C	+/-1C	+/-1C	
Infrared Remote Control Option	Yes	Yes	Yes	Yes	Yes	Yes	
Adjustable Switching Differential	Yes	Yes	Yes	Yes	Yes	Yes	
Changeover Option	No	Yes	No	No	No	No	
Supply	230v	230v	230v	12v	12v	12v	

Dimensions: 98x85x13mm (all units): Weight: 195g (all units).

10004A|0415-030