





## Premium levelling compound datasheet

Fibre-reinforced, flexible, self smoothing levelling compound. Can be laid in 2 - 50 mm in a single application

**20 KG** 



Application data	
Mixing ratio	20 kg grey powder to 4 - 4.25 litres, cold, clean water
Thickness	2 - 50 mm per single application
Pot life	20 - 30 mins approximately
Walk on time	For light foot traffic, approximately 2 - 2.5 hours at 20°C
Floor coverings	After 24 hours - bonded coverings
Installation temperatures	Min 5°C (protect from direct sunlight and draughts)
Coverage per 20 kg bag	1.6 kg x thickness (min thickness 2 mm) x metre square = material in kg's required
Shelf life	6 months from date of packing (see bottom of bag)
Surface preparation	Clean sound and primed substrates
Priming	AmbiPrime primer diluted or neat (see data sheets)
Application data	By hand or pump application (using appropriate equipment)
Cleaning tools	Wash immediately after use with clean water
Storage	Should be stored under cover, frost free and in dry conditions off the ground
Manufactured	Made in England

**Notes:** Setting times are dependent upon the ambient temperatures, humidity and absorbency of the subfloor. Figures quoted are for 20°C. Lower temperatures will extend the setting times, whilst higher temperatures will accelerate the product.

**Application:** Use the mixed material within 20 - 30 minutes, pour the product onto the primed substrate and spread into place using a trowel.